

Toolbox Nisp - Scilab Revue OPUS

M. Baudin

INRIA

31/03/2009

Outline

1 Scilab

- Overview
- Features
- Logo
- Graphics

2 Nisp dans Scilab

- Activités
- Script (Objectif)
- Script (Réalisation)
- Perspectives

Scilab System

- CeCILL license (free software)
- An open system : new user-defined data types (and operations, with overloading).
- Contributions can be downloaded from Scilab Web site.
- Built on external libraries
- Windows (9X/2000/XP/Vista), GNU/Linux (most Unix systems)
- Source code
- On-line help
- English (French) user manuals
- binary versions available


Scilab Features

- 2-D and 3-D graphics, animation
- Linear algebra, sparse matrices
- Polynomials and rational functions
- Interpolation, approximation
- Simulation: ODE solver and DAE solver
- Scicos: a hybrid dynamic systems modeler and simulator
- Classic and robust control, LMI optimization
- Differentiable and non-differentiable optimization
- Signal processing
- Statistics
- Interface with Fortran, Tcl/Tk, C, C++, Java, LabVIEW


Scilab Logo




Some Graphics



Some Graphics



Some Graphics



Nisp dans Scilab

- Portage Windows standard C90
 - gcc sous Linux : standard C99
 - Microsoft Visual Studio 2008 : standard C90
 - création des projets Visual Studio 2008
 - création des dll, avec export/import explicite
 - remplacement de erfc par calerf
 - remplacement de srandom par srand
 - suppression de l'initialisation par PID
 - utilisation de la macro _USE_MATH_DEFINES pour définir la constante PI
- Licence
 - utilisation de Numerical Recipes
- Flexibilité de la librairie
 - instructions exit
 - affichages dans le terminal

Nisp dans Scilab - Objectif (1/5)

```
1 // Un petit exemple, adapté du document de spécification
2 // OPUS – Chaos Polynomial
3 function y = Exemple (x)
4 y(1) = x(1) * x(2);
5 endfunction
6 // Représentation des paramètres incertains
7 vu1 = randomvariable_new ("Normale", [1.0 0.5]);
8 value1 = randomvariable_getvalue(vu1);
9 vu2 = randomvariable_new ("Uniforme", [1.0 2.5]);
10 value2 = randomvariable_getvalue(vu2);
11 // Création d'une collection de variables aléatoires
12 gu = setrandomvariable_new ();
13 gu = setrandomvariable_add (gu, vu1);
14 gu = setrandomvariable_add (gu, vu2);
```

Nisp dans Scilab - Objectif (2/5)

```
1 // Représentation des variables stochastiques
2 vx1 = randomvariable_new("Normale");
3 vx1 = randomvariable_new("Uniforme");
4 gx = setrandomvariable_new();
5 gx = setrandomvariable_add(gx, vx1);
6 gx = setrandomvariable_add(gx, vx2);
7 // Création du Polynôme de chaos
8 pc = polynomialchaos_new(gx);
```

Nisp dans Scilab - Objectif (3/5)

```
1 // Plan d'expériences
2 degré = 2;
3 gx = setrandomvariable_buildsample(gx , "Quadrature" , degré );
4 gu = setrandomvariable_buildsample(gu , gx );
5 np = setrandomvariable_size(gu );
6 pc = polynomialchaos_setsizetarget(pc , np );
7 nx = polynomialchaos_getdimensioninput(pc );
8 ny = polynomialchaos_getdimensionoutput(pc );
9 indata = zeros(nx );
10 outdata = zeros(ny );
11 for k=1:np
12     indata = setrandomvariable_getsample(gu , k );
13     outdata = Exemple1(indata );
14     pc = polynomialchaos_settarget(pc , k , outdata );
15 end
```

Nisp dans Scilab - Objectif (4/5)

```
1 // Analyse des coefficients
2 pc = polynomialchaos_setdegree(pc, degré);
3 pc = polynomialchaos_compute(pc, gx, "Integration");
4 // Edition de l'analyse de sensibilité
5 average = polynomialchaos_getmean(pc);
6 var = polynomialchaos_getvariance(pc);
7 mprintf("Mean = %e\n", average);
8 mprintf("Variance = %e\n", var);
9 mprintf("Indice de sensibilité du 1er ordre\n");
10 isx1 = polynomialchaos_getindicefirstorder(pc, 1);
11 isx2 = polynomialchaos_getindicefirstorder(pc, 2);
12 mprintf("Variable x1 = %e\n", isx1);
13 mprintf("Variable x2 = %e\n", isx2);
```

Nisp dans Scilab - Objectif (5/5)

```
1 // Tracé des données
2 inputx1 = zeros(np);
3 inputx2 = zeros(np);
4 for k=1:np
5     indata = setrandomvariable_getsample(gu , k );
6     inputx1(k) = indata(1);
7     inputx2(k) = indata(2);
8 end
9 plot(inputx1 , inputx2 );
10 histplot(20,inputx1 );
11 histplot(20,inputx2 );
```

Nisp dans Scilab - Réalisation (1/2)

- Interface de la classe RandomVariable
- Windows, Linux

Nisp dans Scilab - Réalisation (2/2)

```
1 // Try randvar_getlog
2 vu1 = randvar_new("Normale",1.0,0.5);
3 randvar_getlog(vu1);
4 randvar_destroy(vu1);
5
6 // Try randvar_getvalue
7 vu1 = randvar_new("Normale",1.0,0.5);
8 nbshots = 1000;
9 values = zeros(nbshots);
10 for i=1:nbshots
11     values(i) = randvar_getvalue(vu1);
12 end
13 computed = mean(values);
14 assert_close ( computed , 1.0 , 1.e-1 );
15 computed = st_deviation ( values );
16 assert_close ( computed , 0.5 , 1.e-1 );
17 randvar_destroy(vu1);
```

Perspectives

- Décision du projet OPUS
- Modifier la librairie NISP (licences, exit, cout, etc...)
- Interfacer la classe SetRandomVariable
- Interfacer la classe PolynomialChaos
- Tests unitaires
- Tests de validation
- Documentation
- Mise en ligne

OPUS project

